

# PHOENIX ASPHALT MAINTENANCE CO., INC.

~ ASPHALT MAINTENANCE INNOVATIONS ~

## CARBONSEAL™

### ASPHALT PAVEMENT SURFACING MATERIAL

#### ~ COMPONENT TECHNOLOGY ~

- Spray or squeegee applied
- Rapid curing
- Skid resistant
- Unmatched wearability
- No scuffing
- Deep black color

#### ~ SPECIFICATIONS ~

- Bulk density 11.4 lbs
- Solids 60%
- Residue on base 65%
- Pen of residue <25%
- ISSA-WTA <5% loss



Municipal & Commercial Applications

Application of CARBONSEAL™ on a properly prepared asphalt surface is usually one coat only due to its 11.4 lbs/gal bulk density. Application rates will depend on asphalt pavement condition and age. Surface should be cleaned thoroughly prior to application.

The asphalt binder system used in CARBONSEAL™ has undergone over 12 years of repetitive lab testing and field evaluations within the end-product field of use.



Residential Applications



Portland Office  
Bend Office

[www.phxasphalt.com](http://www.phxasphalt.com)

503.289.6696 • 866.289.6767 • 503.289.6766 fax  
541.322.9032 • 541.410.5133 • 541.383.9302 fax